

PRODUCT DESCRIPTION

BF PRINTFLOCKSUBLI is a heat transfer film printable with sublimation inks, with a flocked finish that gives a velvet effect that is soft to the touch and pleasant to the eye.

Printing with sublimation inks can be done using sublimation paper or with direct printing.

The paper support facilitates the weeding process. After cutting and weeding, the product can be placed on the garment by transferring it with the BF MYLAR, which must then be removed hot.

APPLICATION STEPS

- Print on sublimation paper or directly on the film - mirror
- Transfer the graphic on the film via sublimation, at 200°C for 30 seconds
- Cut - 60° blade
- Apply BF MYLAR - remove air bubbles
- Remove from liner
- Turn on your heat press - heat to 160°C/320°F
- Place your graphic on the shirt
- Press it - 160°C/320°F for 16 seconds
- Remove BF MYLAR - hot

SIZES


H 50 cm	L 10 mt / 5 mt / 2,5 mt
H 75 cm	/
H 100 cm	/
H 150 cm	/

SAFETY NOTICE




The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev_2021/03






TECHNICAL DATA

	Film: Rayon
	Thickness: ~600μ (±5%)
	Liner: paper
	Finish: velvet
	Inks: sublimation

PLOTTER SETTING

	Cut settings: mirror (on sublimation paper)
	Blade: 60°
	Minimum cut: 1 cm

APPLICATION

	Temperature: 160°C - 320°F
	Time: 16''
	Liner removal: hot
	Pressure: low - 1,5 bar - 20 PSI
	Textile: organic, synthetic, mixed

WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature*	40°C - 104°F
Dry clean	✗
Dryer	✗

*Temperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

BF PRINTFLOCKSUBLI
PRINT&CUT

- *Velvet effect*
- *You can manually set your graphic*
- *Print directly on the film or use sublimation paper*